# **MarineNav CG Elite 12**

### Marine Display



C-026\_MN\_CG\_Elite\_12-PR1





# MarineNav builds tough, true marine-grade displays capable of performing in the harshest environments on earth.

Internationally known for their quality and reliability, our displays are precision built from high strength marine-grade aluminum and finished in salt rated, UV protected powder coating inside and out. Developed to suit a variety of vessels from climate-controlled luxury yachting to more demanding IP65 rated open flybridge military/naval applications and everything in between, there is a MarineNav display suitable for your needs.

The CG Elite Series is our premium class of marine-grade LCD displays featuring optical bonded resistive touchscreen technology that performs even with gloves on. Seeing is believing with our high bright sunlight-readable display. Standard features include one-touch input selection, dedicated backlit front controls that are easy to see and use, and one-touch red monochrome night mode ideal for low light conditions. All MarineNav displays come with a two-year warranty (2nd year with product registration).\*

The CG Elite Series displays are available in 12", 15" and 19" sizes and offer several options including enhanced brightness, front and/or rear IP 65 water-resistance, and composite inputs.

#### CG Elite 12 Features

- 1200 nits brightness (upgradeable)
- 1 VGA, 1 HDMI, 1 DVI, 2 composite
- Optical bonded resistive touchscreen
- Sunlight-readable performance
- IP65 water-resistant front (optional IP65 water-resistant rear)
- Backlit front controls
- Console flush or VESA mounting options
- Available in DC
- Red monochrome night-mode
- TFT active matrix panel, LED backlight
- Two year warranty (2nd year with product registration\*)





# **CG Elite 12 Marine Display**

# Specifications



Features	CGE-12
LCD Display	12.1" TFT Active Matrix Panel, LED backlight
Integrated Computer	Not available
Brightness	1200 nits (upgradeable)
Contrast	1000:1
Aspect Ratio	4:3
Resolution	1024 x 768 native
Optimized Multi-Resolution	Up to 1920 x 1200 supported with scaling
View Angle	160(H), 160(V)
Display Colours	262K
Operating Temperature	-10°C to 55°C (14°F to 131°F)
Video Inputs	1 VGA, 1 HDMI, 1 DVI, 2 Composite
Other Inputs	Power, USB
Input Power	9~30V DC
Power Consumption	35~40 watts
Dimming	Wide dimming range to black
Front Window	Optical bonded resistive touch screen
Bezel & Rear Case	High grade marine aluminum
Finish	Salt rated, UV protected powder coating (internal and external)
Enclosure Options	IP65 water-resistant front (optional IP65 water-resistant rear)
Touchscreen	Resistive, polarized; usable with gloved hand
Backlit Front Controls	Yes, with one-touch hotkeys
Bezel Dimensions	312 mm x 262 mm (12.28" x 10.31") 294 mm x 244 mm (11.57" x 9.60") 63 mm (2.49")
Chassis Dimensions	294 mm x 244 mm (11.57" x 9.60")
Install Depth	63 mm (2.49")
Installation Options	Console flush mount, VESA 75
FCC, CE Approved	Yes
Warranty	2 years (2nd year with registration)*

MarineNav products are available in a multitude of configurations to provide maximum flexibility and user convenience Contact us or visit our website at www.marinenav.ca for more details.

MarineNav Ltd. is an ISO 9001:2015 certified company. Our certified Quality Management System ensures that each unit we produce adheres to the strictest standards and complies with customer requirements. While we strive to ensure the accuracy of all items and descriptions in this document, this is not always possible. Specifications, options, and availability are subject to change without notice. Errors and omissions excepted. We reserve the right to limit quantities.



Red Monochrome Night Mode View



**Backlit Front Controls** 







1466 Panmure Island Rd – Rte 347 Panmure Island PE COA 1RO 902 838-7011 www.marinenav.ca

<sup>\*</sup> Product must be registered within first warranty year. Conditions apply. Contact a MarineNav representative or authorized distributor for full details.