

# Oceanus ROV Accessories

## Neutral Buoyancy ROV Tether



BUILT  
NORTH ATLANTIC  
TOUGH  
TRUSTED  
EVERWHERE

D-001\_ROV\_ACC\_NB-Tether\_2026-PR1

**Manufactured on-site, neutrally buoyant tether segments can be ordered to single lengths to a maximum of 500m.**

A neutrally buoyant tether cable connects the ROV to the topside ROV control case providing communications, video, and an auxiliary pair of independent conductors for accessory use. The neutral tether cable consists of conductors, an Aramid strength member, a flotation material, and an outer jacket.

MarineNav tether cable segments can connect to a horizontal distance of 500 meters (1640 ft). The vertical tether distance is limited to the submersibles depth rating (ie: 400 meters [1312 ft] for the Oceanus Pro ROV).



### 8-Pin Neutral Buoyancy Tether - Standard Pre-cut Tether Lengths (with product code)

10 meters	ROV-TETHER-NEU-10M
20 meters	ROV-TETHER-NEU-20M
40 meters	ROV-TETHER-NEU-40M
75 meters	ROV-TETHER-NEU-75M
100 meters	ROV-TETHER-NEU-100M
150 meters	ROV-TETHER-NEU-150M
200 meters	ROV-TETHER-NEU-200M
300 meters	ROV-TETHER-NEU-300M

Contact MarineNav regarding requests for custom lengths and current pricing on all products.

**MARINENAV**  
BUILT NORTH ATLANTIC TOUGH.  
TRUSTED EVERYWHERE.



© 2026 MarineNav Ltd.

1466 Panmure Island Rd – Rte 347  
Panmure Island PE COA 1R0  
902 838-7011  
[www.marinenav.ca](http://www.marinenav.ca)